

Same  
Formula  
NEW LOOK!!

## FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY

**CONTAINS:** Isoparaffinic Hydrocarbon (64741-66-8), Lithium Grease (N/A), Food Grade Mineral Oil (8042-47-5), and Aliphatic Mineral Spirits (64742-88-7).

**DANGER:** Do not take internally. Avoid contact with eyes. Avoid breathing vapors. Vapor is heavier than air and may collect in low lying areas. Keep away from heat, sparks and open flame.

### FIRST AID:

**IF EYE CONTACT:** Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. Get medical attention immediately.

**IF SKIN CONTACT:** Wash with plenty of soap and water. If irritation persists seek medical attention.

**EXCESSIVE INHALATION:** Remove to fresh air. If continued difficulty is experienced, seek medical attention immediately. If breathing stops give artificial respiration.

**IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

**HMIS RATING:** Health, 1; Flammability, 3; Reactivity, 0; Personal Protection, B.

### HANDLING AND STORAGE:

Keep container closed except when in use. Do not store in unmarked containers. Store in a cool, dry place. Do not cut or weld on or near container, even when empty.

For further information,  
consult Material Safety Data Sheet



# CHAIN and CABLE LUBRICANT

286505

Foaming Action

Non-Chlorinated

Rust Protective Coating

Fortified With Moly

Penetrates • Lubricates



**TECHNO SOLUTIONS WORLD**

PO Box 375122 Cayey, PR 00737-5122  
P. 787-738-0087, 0088 Fx. 1-888-456-0656  
[www.technosw.com](http://www.technosw.com) , [sales@technosw.com](mailto:sales@technosw.com)

A mixture of penetrants, anti-oxidants, oils and greases plus Molybdenum Disulfide particles which creep into chain components and cable strands to provide excellent lubrication and rust prevention.

Molybdenum Disulfide adds extra wear resistance and withstands much higher pressure and temperature than simple lubricating oils.

Will not break down when exposed to high humidity, salt spray and chemical vapors or water.

**USE ON:** Heavy duty machinery and equipment, booms, winches, cranes, wire rope, metal conveyors, scrap iron, shears, steam shovels, chain saws, cutter bars, conveyors, hoist chains, link and roller assemblies; railroad, mining, aircraft handling, material handling equipment; road and construction machinery.

### DIRECTIONS:

LUBRICATION IS MOST EFFECTIVE  
WHEN PARTS ARE CLEAN BEFORE  
APPLICATION

1. Agitate before use.
2. Never mix with other chemicals.
3. Spraying produces the most uniform application. When spraying, use either an airless or compressed air sprayer. Product may also be brushed on.
4. Always keep contained closed when not in use to prevent evaporation or contamination.