



FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY

DANGER: Contains Ethyl Alcohol (64-17-5), Polyalkylene Glycol Monobutyl Ether (9038-95-3) and Amine containing Alcohol (Trade Secret). Use only in a well ventilated area. Avoid breathing vapors. Do not use near heat, sparks or open flame. Do not take internally. Avoid contact with eyes or prolonged contact with skin.

FIRST AID:

IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

IF SKIN CONTACT: Wash with soap and water. If irritation persists seek medical attention.

EXCESSIVE INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

IF INGESTED: Do not induce vomiting. Seek medical attention immediately.

RECYCLING: Do not puncture or incinerate container. Consult local authorities for proper disposal of empty containers.

HANDLING AND STORAGE:

Keep container closed except when in use. Do not store in unmarked containers. Store in a cool, dry place. Do not cut or weld, on or near container, even when empty.

HMS RATING: Health, 1; Flammability, 3; Reactivity, 1; Personal Protection, B.

For further information, consult Material Safety Data Sheet



CUTTING and TAPPING FLUID

287505

Cools • Lubricates

Clear • Non-Staining

Rinses Away With Water

TECHNO SOLUTIONS WORLD

PO Box 375122 Cayey, PR 00737-5122
P. 787-738-0087, 0088 Fx. 1-888-456-0656
www.technosw.com , sales@technosw.com

A clear, synthetic coolant and lubricating fluid for machining, punching, sawing, milling, boring, cutting, grinding, tapping and threading operations on all steels and non-ferrous metals.

Results in cooler work piece, less heat distortion and less tool burning which increases production rates and tool life.

Transparency of fluid allows for excellent visibility of work area.

Use extensively for portable operations, field operations and any cutting, drilling or tapping machinery equipped with its own recycling system. Fluid can be removed with cold water or degreasing solvents.

COOLS THESE SURFACES: Aluminum and Aluminum Alloys, Carbon Steels, Stainless Steels, Chrome-Moly and Vanadium Steels, Nitralloy Steel, Inconel, Monel, Phosphor, Bronze, Titanium, Hastelloy Alloys, Beryllium, Copper and other related alloys.

DIRECTIONS:

Product can be sprayed on, brushed on or used in automatic recirculating systems. Apply a liberal amount directly to work area, Reapply as necessary to keep area cool and well lubricated.