

TERAND

The Maintenance Professional's Choice



TECHNO SOLUTIONS WORLD

PO Box 375122 Cayey, PR 00737-5122
P. 787-738-0087, 0088 Fx. 1-888-456-0656
www.technosw.com, sales@technosw.com

PENETRATING GEL LUBRICANT WITH PTFE

94713

FOR USE BY:

- Machine Shops
- Light and Heavy Manufacturing
- HVAC, Plumbing and Other Trades
- Automotive
- All Repair Operations



- High Tack
- Effective at Temperatures from -30°F to +500°F
- Penetrates as an Oil then Sets up to a Tacky Grease-Like Gel

A high tack lubricating gel that provides superior lubrication from -30°F to +500°F. Penetrates as an oil to lubrication point then forms into a tacky, grease-like gel. Contains PTFE for added friction reduction. Provides superior stringing action. Resists water washout and weathering. Residual film prevents rust and corrosion. Safe on most plastics and paints.

FOR USE ON:

- Chains • Gears • Hinges
- Sprockets • Cable • Wire Rope
- Slides • Valves • Bushings
- Pistons • Shafts • Rings



- Clear Stringing Gel
- Resists Water Washout
- Provides a Moisture Resistant Film
- Protects Against Rust and Corrosion