A heavy-duty, fast-acting, flush action aerosol that quickly cuts through and removes tough grease, oil, tar, asphalt, adhesives and mastic, wax, ink, fresh paint and more!

Provides high solvency and a powerful spray that blasts away grime then dries fast, residue-free. Fortified with citrus terpene to enhance cleaning and reduce solvent odor.

Will not harm most painted surfaces. Contains no chlorinated solvents or ozone depleting substances.

USE ON: Industrial Equipment, Automotive Parts, Printing Presses, Oil Field Equipment, Generators, Metal Parts, Tools, HVAC Equipment, Construction and Road Building Machinery, Farm and Asphalt Equipment, Packaging Equipment and more!

DIRECTIONS:

Spray a heavy burst of spray onto surface, allowing to penetrate through dirt. Wipe or allow to air dry. For heavily encrusted areas, agitate with a brush, then rinse off with a second spray.

NOTE: This solvent is extremely flammable. To prevent flash fire, do not spray onto any electrified or energized equipment or parts. Electrical equipment treated with this product MUST be completely dry before reenergizing.



DANGER: Contains Aliphatic FIRST Petroleum Distillates (64742- CONTACT: Flush with 89-8), Liquefied Petroleum Gas amounts of cool running water (68476-86-8) and Citrus for at least 15 minutes while Terpene (5989-27-5). Extremely holding upper and lower lids Flammable. Do not spray near open. If irritation persists get sparks, heat or open flame, medical attention immediately, Contents under pressure. IF SKIN CONTACT: Wash with Exposure to heat may cause soap and water. If irritation bursting. Do not puncture, persists seek medical attention. incinerate or store above 120°F. EXCESSIVE Avoid prolonged exposure to Remove to fresh air. Seek sunlight. Avoid skin and eye medical attention immediately. If contact. Do not take internally. breathing stops give artificial Harmful if swallowed.

AID: IF EYE large INHALATION: respiration. IF INGESTED: Do not induce vomiting. Seek medical attention immediately.

For further information consult Material Safety Data Sheet.

KEEP OUT OF REACH OF CHILDREN



ŝ	HEALTH	1
HMIS KALING	FLAMMABILITY	3
	REACTIVITY	0
M	PERSONAL PROTECTION	в
le		

Techno Solutions World

PO Box 375122 Cayey, PR 00737-5122 P. 787-738-0087, 0088 Fx. 1-888-456-0656 www.technosw.com , sales@technosw.com



Formula NEW LODK! OLVENT egreaser CITRUS-BASED 53415

Fast-Acting

Solvent Degreaser with Flush Action

Cuts Through Grease, Oil. Tar

Quick, Residue Free Drying

DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE. SEE OTHER CAUTIONS ON BACK PANEL. NET WT. 15 OZ. (425 Grams)