



FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY

STAINLESS STEEL COATING
UN-1263 PAINT • FLASH POINT 45°F.

DANGER: FLAMMABLE LIQUID AND VAPOR. Contains: Toluene (108-88-3), Xylene (1330-20-7), Ethyl Benzene (100-41-4) Mineral Spirits (64742-47-8) and Chromium (7440-47-3). VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat, sparks, and flame. VAPORS MAY CAUSE FLASH FIRE. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

Use only with adequate ventilation. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

FIRST AID:

IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. Get medical attention immediately.

IF SKIN CONTACT: Wash with soap and water. If irritation persists seek medical attention.

EXCESSIVE INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

IF INGESTED: Do not induce vomiting. Seek medical attention immediately.

HMIS RATING: Health, 2; Flammability, 3; Reactivity, 0; Personal Protection, B.

KEEP OUT OF REACH OF CHILDREN

For further information consult Material Safety Data Sheet.



STAINLESS STEEL COATING

297405

Long Lasting

Super Tough Epoxy Formula

Protects Against: Rust,
Corrosion and Chemical
Damage

TECHNO SOLUTIONS WORLD

PO Box 375122 Cayey, PR 00737-5122
P. 787-738-0087, 0088 Fx. 1-888-456-0656
www.technosw.com, sales@technosw.com

STAINLESS STEEL EPOXY COATING

A high leafing, pure 316 Stainless Steel Flake, combined with a super tough epoxy resin. Provides a hard resistant coating that seals surfaces against corrosion, harsh weather, chemical damage and abrasion. A revolutionary, one package ready to use product that requires no measuring or addition of other ingredients. Flows over and coats surfaces smoothly and evenly. Dries to the touch in 30 minutes. Hardens overnight. Cures to optimum hardness after several days.

EXCELLENT ADHESION TO: Metal, Wood, Ceramics, Concrete, Hard Plastic

APPLICATIONS: Steam Pipes, Radiators, Fire Hydrants, Exhaust Fans, Mufflers, Parking Meters, Wire Fences, Boilers, Engines, Water Lines, Grills, Lockers, Heat Exchangers, Ovens, Tanks, Chemical Processing and Production Equipment.

DIRECTIONS:

AGITATE BEFORE AND DURING USE.
DO NOT THIN!

1. Clean surfaces thoroughly prior to application. Remove grease and oil with degreasing solvent. Remove all paint with paint remover then clean surface with degreasing solvent. Remove all loose rust with a wire brush or by sandblasting heavily corroded areas.
2. Creamy suspension lends itself to brush coating as well as spraying. Do not use in plastic sprayers. Dries to the touch in 30 minutes. For maximum toughness and resistance allow surface to dry for several days.
3. Keep container closed when not in use to prevent evaporation and hardening.

RECYCLING: Do not puncture or incinerate container. Consult local authorities for proper disposal of empty containers.

HANDLING AND STORAGE:

Keep container closed except when in use. Do not store in unmarked containers. Store in a cool, dry place. Do not cut or weld, on or near container, even when empty.