



PO Box 375122 Cayey, PR 00737-5122 P. 787-738-0087, 0088 Fx. 1-888-456-0656 www.technosw.com , sales@technosw.com

RTV SILICONE GASKET MAKER

11407 - 11607

FORMS IN-PLACE GASKETS and SEALS FOR: Pumps, High pressure pipe joints, oil and transmission pans, oil and water pumps, valve and timing chain covers, electric motors and electrical control boxes, gear boxes, compressors, machine covers, rigid flange assemblies and equipment housings.

NOT RECOMMENDED FOR USE ON: Cylinder heads, exhaust manifolds, intake manifolds, carburetors or parts requiring continuous immersion in gasoline.

This product meets the requirements of FDA Regulation 21 CFR, 177.2600 when fully cured and washed. This formulation has been fully certififed to Federal Specification TT-001543A Class A (COM-NBS), TT-S-00230 Class A (COM-NBS) for silicone building seglants and MIL-A-46106A.

RTV - Silicone Gasket Maker can be used on emtal, glass, porcelain, ceramics, wood, rubber, and most paints and plastics. As an instant gasket maker, this product replaces a wide range of cork, paper, asbestos, felt, and metal gaskets. Features excellent adhesion characteristics, high chemical resistance and will not sage or shrink. The High Temp Red can withstand intermittent temperatures up to 650°F. All colors can withstand pressures up to 350 psi. Offers unmatched performance under the most severe operating conditions. Virtually unaffected by chemical deterioration, extreme weather, temperature or aging. Safe on oxygen sensors and meets GM and many OEM specifications.



11407 - BLUE 11507 - RED

11607 - BLACK

- Blue And Black Remain
 Permanently Flexiable at
 Temperatures From -60°F to 500°F
 (Red -60°F To +650°F)
- Reduces Inventory Eliminates Need to Stock Conventional Gaskets and Seals
- Reduces Down Time Gets
 Equipment Back in Operation Fast
- 100% Of Gaskets And Seals in Each Can
- 100% R.T.V. (Room Temperature Vulcanizing) Silicone - Industrial Strength Sealant
- Pressurized Dispenser Makes any Size or Shape Gasket Instantly